

# PRV

PATENT- OCH REGISTRERINGSVERKET

Patentavdelningen

## Intyg Certificate

*Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.*

*This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.*

(71) *Sökande*                      *XCounter AB, Danderyd SE*  
*Applicant (s)*

(21) *Patentansökningsnummer*    *0302670-5*  
*Patent application number*

(86) *Ingivningsdatum*                      *2003-10-08*  
*Date of filing*

*Stockholm, 2003-10-15*

*För Patent- och registreringsverket*  
*For the Patent- and Registration Office*

*Hjördis Segerlund*  
*Hjördis Segerlund*

*Avgift*  
*Fee*            *170:-*

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Tom FRANCKE  
Application No.: NEW APPLICATION  
Filed: October 30, 2003  
For: SCANNING-BASED DETECTION OF IONIZING RADIATION

**PRIORITY LETTER**

October 30, 2003

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Dear Sirs:


Pursuant to the provisions of 35 U.S.C. 119, enclosed is/are a certified copy of the following priority document(s).

<b><u>Application No.</u></b>	<b><u>Date Filed</u></b>	<b><u>Country</u></b>
0302670-5	10/8/2003	Sweden

In support of Applicant's priority claim, please enter this document into the file.

Respectfully submitted,

HARNESS, DICKEY, & PIERCE, P.L.C.

By   
John A. Castellano, Reg. No. 35,094  
P.O. Box 8910  
Reston, Virginia 20195  
(703) 668-8000

JAC/jj

**SCANNING-BASED DETECTION OF IONIZING RADIATION****FIELD OF THE INVENTION**

The invention relates generally to apparatuses and methods for scanning-based detection of radiation.

**5 BACKGROUND OF THE INVENTION AND RELATED ART**

Various line detectors for detecting ionizing radiation are known in the art. A particular kind of line detector is the gaseous-based parallel plate detector, wherein electrons freed as a result of the interaction between an incident beam of ionizing radiation and the gas of the detector, are accelerated in a direction substantially perpendicular to the incident radiation beam and subsequently detected. This line detector is often referred to as an edge-on detector since the incident radiation beam enters the detector sideways between the plates or electrodes thereof, i.e. the radiation impinges on an edge of the detector.

The spatial resolution of such and other detectors with an edge-on incidence of radiation is often an important parameter. In many examinations it is desirable to obtain a spatial resolution, which is better than 100 microns, e.g. as good as 50 microns. This put very high demands on the detector being used - both in terms of a narrow radiation sensitive area and in terms of small detecting elements or pixels.

Therefore, the detectors are typically provided with a detecting or readout arrangement comprising a number of readout strips, which are pointing towards the used X-ray source and are broader at the far end of the detector than at the front end thereof, see e.g. U.S. Pat. No 6,118,125 by Carlson et al. Hereby, any

parallax errors, which may be introduced due to the divergence of the incident X-ray beam, are avoided.

#### SUMMARY OF THE INVENTION

However, a severe drawback with the detectors using readout  
5 strips in a fan-shaped configuration described above is that each detector can be designed for one distance only between the radiation source and the detector. Such detector provides for an optimum spatial resolution only at this distance. If the  
10 radiation source is moved away from or towards the detector the strips are no longer pointing towards the radiation source and the spatial resolution is heavily deteriorated. The detector becomes practically useless if the distance is altered considerably.

A main object of the invention is therefore to provide a  
15 scanning-based ionizing radiation detecting apparatus and method, which provide for measurement of high spatial resolution independently of the distance from the detector to the radiation source used.

A further object of the invention is to provide such scanning-  
20 based ionizing radiation detecting apparatus and method, which provide a novel mechanism for increasing and decreasing the achievable signal-to-noise ratio, the spatial resolution and the detecting time of the detecting apparatus.

These objects, among others, are attained by apparatuses and  
25 methods as claimed in the appended claims.

By providing a scanning-based radiation detector apparatus for  
recording an image of an object comprising a one-dimensional  
detector exposed to a fan-shaped beam of ionizing radiation from  
a radiation source as transmitted through the object, the  
30 detector being of the kind wherein charges or photons generated

by interactions between the fan-shaped radiation beam and a detection medium and traveling in a direction essentially perpendicular to the fan-shaped radiation beam; and a device for moving the detector and the fan-shaped radiation beam relative to the object while the detector is arranged to repeatedly detect to thereby create an image of the object, wherein the detector has a detecting arrangement for detecting the generated charges or photons, which comprises a large number of individual detecting elements, which can be grouped together to form a plurality of detecting stripes located side-by-side and pointing towards a selected single point, which coincides with the location of the radiation source, measurements of very high spatial resolution can be performed. The individual detecting elements are grouped together depending on the distance between the detector and the radiation source, and thus a single detector can be optimized for any given detector-radiation source distance.

Further, the plurality of detecting stripes, which are grouped together from the large number of individual detecting elements, may have a width corresponding to a selected required spatial resolution or signal-to-noise ratio. The narrower the stripes are, the better spatial resolution can be obtained, but to the cost of a deteriorated signal-to-noise ratio given a constant radiation flux. The wider the stripes are, the better signal-to-noise ratio can be obtained, but to the cost of a deteriorated spatial resolution. Still further, the plurality of detecting stripes, which are grouped together from the large number of individual detecting elements, are of a number, which corresponds to a selected required maximum detecting time given a detector such as a CCD-based detector, where the readout time can be affected by the grouping of individual detecting elements or pixels.

The one-dimensional detector is preferably, but not exclusively, a gaseous-based parallel plate detector. Other detectors that may be used include liquid-based parallel plate detectors, scintillator-based arrays, diode arrays, CCD arrays and other solid-state detectors with edge-on or near edge-on incidence of X-rays.

Further characteristics of the invention, and advantages thereof, will be evident from the detailed description of preferred embodiments of the present invention given hereinafter and the accompanying Figs. 1-4, which are given by way of illustration only, and thus are not limitative of the present invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 illustrates schematically, in a side view, an apparatus for scanning-based X-ray imaging according to a preferred embodiment of the present invention.

Fig. 2 is a schematic enlarged cross-sectional view of some of the components of the apparatus of Fig. 1 taken along the line A-A of Fig. 1.

Fig. 3 is a schematic enlarged cross-sectional view of the same components of the apparatus of Fig. 1, but taken in an orthogonal direction as compared with the Fig. 2 view. Also a readout arrangement of a detector comprised in the apparatus of Fig. 1 is illustrated at a first operation setting.

Fig. 4a is a schematic enlarged top view of a readout arrangement of a detector comprised in the apparatus of Fig. 1 at a second operation setting.

Fig. 4b is a schematic enlarged top view of the readout arrangement of the detector comprised in the apparatus of Fig. 1 at a third operation setting.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

5 From top to bottom the apparatus in Fig. 1 comprises an X-ray source 11, a filter device 12, a fan beam collimator 13, an object table or holder 15, and a one-dimensional detector 16.

The X-ray source 11 is a conventional X-ray tube having a cathode, which emits electrons, and an anode emitting X-rays in  
10 response to being struck by said electrons. The resulting X-ray beam 24 is divergent.

The filter device 12 is located just beneath the X-ray tube 11, which typically includes thin metallic foils acting as filters to absorb the lowest and optionally also the highest energy  
15 photons, which do not contribute significantly to the image quality.

The fan beam collimator 13 may be a thin foil of e.g. tungsten with a narrow radiation transparent slit etched or cut away. The slit is aligned with a corresponding entrance of the detector 16  
20 so that X-rays passing through the slit of the fan beam collimator 13 will enter the detector 16. However, due to the divergence of the radiation beam 24 the narrow radiation transparent slit has to be shorter and thinner than the entrance of the detector.

25 The detector 16, which will be described more in detail below, is a gaseous-based parallel plate detector arranged for repeated one-dimensional imaging of the radiation beam 24, being fan-shaped downstream of the collimator 13.

The X-ray tube 11, the fan beam collimator 13 and the detector 16 are attached to a common E-arm 17, which in turn is rotatably attached to a vertical stand 18 by means of a spindle 19 approximately at the height of the X-ray tube 11. In this manner, the X-ray tube 11, the fan beam collimator 13 and the detector 16 can be moved in a common pivoting movement relative to an examination object arranged on the object table 15 to scan the object and produce a two-dimensional image of the radiation transmitted through the object. The pivoting movement is schematically indicated by arrow 23.

The object table 15 is firmly attached to a support 20, which in turn is firmly attached to the vertical stand 18. For this purpose the E-arm 17 is provided with a recess or similar in the E-arm 17 (illustrated by the dashed lines). During scanning, the examination object (not illustrated) is located on the object table 15, which is kept still during scanning. Alternatively, the object is moved during scanning, while the X-ray tube 11, the fan beam collimator 13 and the detector 16 are kept at rest.

It shall be appreciated that the detector apparatus of Fig. 1 may be modified and arranged for linear movement of the X-ray tube 11, the fan beam collimator 13 and the detector 16 with respect to the object being examined. Yet alternatively, the fan beam collimator 13 and the detector 16 may be rotated 16 in the horizontal plane with respect to the object being examined.

Furthermore, the detector apparatus comprises a microprocessor or computer 21 provided with suitable software for controlling the apparatus and readout and post-processing of the signals from the line detector 16 and a power supply 22 for supplying the detector and the microprocessor or computer 21 with power and for driving a step motor or similar housed in the vertical stand 18 for driving the spindle 19 and thus the E-arm 17.



The detector 16 is illustrated more in detail in Figs. 2-3 and is oriented such that the planar or fan-shaped X-ray beam 24 can enter sideways between essentially planar cathode 25, 26 and anode 27, 28 arrangements. Each of the electrode arrangements 25, 26; 27, 28 includes an electrically conducting electrode layer 25, 27 supported by a respective dielectric substrate 26, 28, wherein the arrangements are oriented so that the conductive cathode 25 and anode 27 layers are facing each other. A radiation transparent window 30 is provided at the front end of the detector to form an entrance for the fan-shaped beam 24 to the detector 16.

Preferably, the dielectric substrates 26, 28 and the window 30 define together with sidewalls 29 a gas-tight confinement capable of being filled with an ionizable gas or gas mixture. Alternatively, the electrode arrangements are arranged within an external gas-tight casing (not illustrated). The ionizable gas or gas mixture may e.g. comprise krypton and carbon dioxide or xenon and carbon dioxide.

The detector 16 comprises further a detecting or readout arrangement including a two-dimensional array of a large number of electrically insulated detecting or readout elements 27a as can be seen in Fig. 3. Typically, the anode arrangement 27, 28 constitutes the readout arrangement. Each of the readout elements 27a is preferably connected to the readout and signal-processing computer 21 as being illustrated in Fig. 1, whereupon the signals from each readout 27a can be processed separately.

Alternatively, the readout arrangement is arranged separately from the anode 25, but adjacent anode 27 or adjacent cathode 25, or elsewhere. The detector 16 may also comprise capabilities for electron avalanche amplification in order to record very low

flux of X-rays, or detect each single X-ray with high efficiency.

The large number of individual detecting elements 27a are, according to the present invention, grouped together to form a plurality of detecting stripes or readout strips 27b side-by-side, where the stripes 27b are all pointing towards a selected single point, and each of them provides for a single signal value during detection. The grouping may be effectuated in the detector hardware or in the software of the computer 21 depending on the particular detector apparatus used.

In Fig. 3 seventeen such strips 27b are illustrated alternately using black and white filled readout elements for illustrative purposes (nine black strips and eight white strips interposed between the black ones). When the selected point now coincides with the location of the radiation source, any parallax errors in detected images are compensated for, thereby providing for an increased spatial resolution. The readout strips extend in directions parallel with the direction of incident photons of the X-ray beam 24 at each location. Given the divergent beam 24 from the radiation source 11 the readout strips 27b are arranged in a fan-like configuration. Further, for the same reason the readout elements 27a are grouped together in a manner so that the resulting readout strips are broader at the far end of the detector than at the front end thereof.

If the distance between the one-dimensional detector 16 and the radiation source 11 is altered, the large number of individual detecting elements 27a is just regrouped to fit that distance. For instance, the readout arrangement is illustrated in Fig. 4a as being used with a radiation source located closer to the detector. Here, seven black strips and six white strips interposed between the black ones are illustrated. As can be

seen they are considerably less parallel than the strips of Fig. 3.

It shall be understood that while the illustrated detector has a limited number of readout elements 27a for sake of simplicity, a preferred detector may comprise at least 1000, preferably at least 10000, more preferably at least 100000, and most preferably at least 1000000, individual readout elements 27a. Each of the readout elements 27a may have a quadratic or rectangular shape and a detecting area, which measures less than 1 mm<sup>2</sup>, preferably less than 0.25 mm<sup>2</sup>, and more preferably less than 0.01 mm<sup>2</sup>, and most preferably less than 0.0025 mm<sup>2</sup>. Thus, the number of readout strips 27b obtained by grouping may be much larger than what is illustrated and the strips will appear with much smoother delimitation. A spatial resolution better than 0.1 mm is easily achievable. If the readout elements 27a are rectangular they are preferably arranged so that their longer sides are parallel with the central axis of the radiation beam 24. Alternatively, each of the readout elements 27a may have a trapezium shape and the readout elements in the far end of the detector may be broader than the readout elements in the front end thereof.

Further, the plurality of detecting stripes, which are grouped together from the large number of individual detecting elements, may have a width corresponding to a selected required spatial resolution or signal-to-noise ratio. The narrower the stripes are, the better spatial resolution can be obtained, but to the cost of a deteriorated signal-to-noise ratio for a given X-ray flux. The wider the stripes are, the better signal-to-noise ratio is obtainable, but to the cost of a deteriorated spatial resolution. In Fig. 4b the readout arrangement is illustrated as being used in a mode with higher signal-to-noise ratio and lower spatial resolution. Here, five black strips and four white

strips interposed between the black ones are illustrated. As can be seen they are considerably broader than the strips of Fig. 3. Thus, given a selected required signal-to-noise ratio for a certain radiation flux or a selected spatial resolution, the required width of the strips to be used can be calculated, and the readout elements 27a may be grouped accordingly.

As the number of strips is reduced, the speed of the detector can be improved depending on the readout mechanism of the detector. Thus, given a selected required maximum detecting time, the maximum number of strips to be used can be calculated, and the readout elements 27a may be grouped accordingly.

In an alternative version of the apparatus of Fig. 1, the detector is replaced by a detector arrangement comprising a plurality of the inventive one-dimensional detector distributed in a one- or two-dimensional array. The fan beam collimator 13 is replaced by a collimator with a plurality of narrow radiation transparent slits - one for each detector. The dimensions and orientations of the slits are such that each detector is exposed to a respective fan-shaped X-ray beam. By such version the scanning distance and time can be considerably shortened.

For further details regarding different kind of detectors for use in the present invention, reference is made to the following U.S. Patents by Tom Francke et al. and assigned to XCounter AB of Sweden, which patents are hereby incorporated by reference: Nos. 6,118,125; 6,373,065; 6,337,482; 6,385,282; 6,414,317; 6,476,397; 6,477,223; 6,518,578; 6,522,722; 6,546,070; 6,556,650; 6,600,804; and 6,627,897.

It shall further be appreciated that while the detector in the description above has been described as a gaseous-based ionization detector, wherein the freed electrons are drifted in a direction essentially perpendicular to the direction of the

incident ionization, the present invention is not limited to such a detector. Examples of detectors that can be used in the present invention include liquid-based parallel plate detectors, edge-on scintillator-based arrays, diode arrays and other solid-state detectors with edge-on or near edge-on incidence of X-rays.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2224  
2225  
2226  
2227  
2228  
222

# CLAIMS

1. A scanning-based radiation detector apparatus for recording an image of an object comprising:

5 - a one-dimensional detector (16) exposed to a fan-shaped beam (24) of ionizing radiation from a radiation source (11) as transmitted through said object, and arranged for repeated one-dimensional imaging of said fan-shaped beam of ionizing radiation, said one-dimensional detector (16) being of the kind wherein charges or photons generated by interactions  
10 between said fan-shaped beam (24) of ionizing radiation and a detection medium and traveling in a direction essentially perpendicular to said fan-shaped beam (24) of ionizing radiation, are detected; and

15 - a device (17-19, 21-22) for moving said one-dimensional detector (16) and said fan-shaped beam (24) of ionizing radiation relative said object while said one-dimensional detector (16) is arranged to repeatedly detect to thereby create an image of the object, characterized in that

20 - said one-dimensional detector (16) has a detecting arrangement (27, 28) for detecting said charges or photons, which comprises a large number of individual detecting elements (27a), and means for grouping said large number of individual detecting elements together to form a plurality of detecting stripes side-by-side, which plurality of detecting  
25 stripes are all pointing towards a selected single point.

2. The scanning-based radiation detector apparatus of claim 1 wherein said selected single point coincides with the location of said radiation source.

3. The scanning-based radiation detector apparatus of claim 1 or 2 wherein said means for grouping is arranged to regroup said large number of individual detecting elements if the distance between the one-dimensional detector (16) and the radiation source is altered.

4. The scanning-based radiation detector apparatus of any of claims 1-3 wherein said means for grouping is arranged to group said large number of individual detecting elements together to form a plurality of detecting stripes, which each has a width corresponding to a selected required spatial resolution or signal-to-noise ratio.

5. The scanning-based radiation detector apparatus of any of claims 1-4 wherein said means for grouping is arranged to group said large number of individual detecting elements together to form a plurality of detecting stripes, which is of a number, which corresponds to a selected required maximum detecting time. 6. The scanning-based radiation detector apparatus of any of claims 1-5 wherein said means for grouping is arranged to group said large number of individual detecting elements together to form a plurality of detecting stripes, which each has a varying width.

7. The scanning-based radiation detector apparatus of any of claims 1-6 wherein said large number of individual detecting elements are distributed in a two-dimensional array.

8. The scanning-based radiation detector apparatus of any of claims 1-7 wherein said large number is at least 1000, preferably at least 10000, more preferably at least 100000, and most preferably at least 1000000. 9. The scanning-based radiation detector apparatus of any of claims 1-8 wherein the detecting area of each of said large number of individual detecting elements measures less than 1 mm<sup>2</sup>, preferably less

than 0.25 mm<sup>2</sup>, and more preferably less than 0.01 mm<sup>2</sup>, and most preferably less than 0.0025 mm<sup>2</sup>

10. The scanning-based radiation detector apparatus of any of claims 1-9 wherein said one-dimensional detector (16) is any of  
5 a gaseous-based parallel plate detector, liquid-based parallel plate detector, a scintillator-based array, a diode array or a solid-state detector.

11. A method for recording an image of an object characterized by the steps of:

10 - indicating a distance between a radiation source (11) of ionizing radiation and a one-dimensional detector (16), wherein the one-dimensional detector (16) is of the kind wherein charges or photons generated by interactions between an incident radiation beam of ionizing radiation and a  
15 detection medium and traveling in a direction essentially perpendicular to the radiation beam of ionizing radiation, are detected; and has a detecting arrangement (27, 28) for detecting said charges or photons, which comprises a large number of individual detecting elements (27a);

20 - grouping said large number of individual detecting elements together to form a plurality of detecting stripes side-by-side depending on said indicated distance;

25 - exposing said one-dimensional detector (16) to a fan-shaped beam (24) of ionizing radiation from said radiation source (11) as transmitted through said object; and

- moving said one-dimensional detector (16) and said fan-shaped beam (24) of ionizing radiation relative said object while said repeatedly detecting by said one-dimensional detector (16) to thereby create an image of the object.



12. The method of claim 11 wherein said large number of individual detecting elements are grouped together to form said plurality of detecting stripes to all point towards said source of ionizing radiation.

5 13. The method of claim 11 or 12 wherein said method is repeated if the distance between the one-dimensional detector (16) and the radiation source is altered.

14. The method of any of claims 11-13 wherein

10 - a required spatial resolution or signal-to-noise ratio is indicated; and

- said large number of individual detecting elements are grouped together to form each of said plurality of detecting stripes with a width depending on said indicated required spatial resolution or signal-to-noise ratio.

15 15. The method of any of claims 11-14 wherein

- a required maximum detecting time is indicated; and


20 - said large number of individual detecting elements are grouped together to form said plurality of detecting stripes in a number, which depends on said indicated required maximum detecting time.

25 16. The method of any of claims 11-15 wherein said large number of individual detecting elements are grouped together to form each of said plurality of detecting stripes with a varying width.

**ABSTRACT**

A scanning-based radiation detector apparatus and method are disclosed. A one-dimensional detector (16) is exposed to a fan-shaped beam (24) of ionizing radiation from a radiation source (11) as transmitted through an object, where the detector (16) is of the kind wherein charges or photons generated by interactions between the radiation beam (24) and a detection medium and traveling in a direction essentially perpendicular to the radiation beam (24), are detected. A device (17-19, 21-22) moves the detector (16) and the radiation beam (24) relative the object while the detector (16) is arranged to repeatedly detect to thereby create an image of the object. According to the invention the detector (16) has a detecting arrangement (27, 28), which comprises a large number of individual detecting elements (27a), and means for grouping the individual detecting elements together to form a plurality of detecting stripes side-by-side, which plurality of detecting stripes are all pointing towards the radiation source (11).

(Fig. 3)



**Fig. 1**

2/4




Fig. 2

3/4






Fig. 3

4/4



**Fig. 4a**



**Fig. 4b**